



## Flasher with LED light.

24 Vac/dc or 230 V power supply.  
High brightness and visibility in any weather conditions.  
Energy and costs saving.

- **Environmental friendly**  
its life is 50 times superior to that of any traditional lamp.
- **Fixed or flashing light.**
- **Practical**

It can be mounted on to a wall or pillar (fittings inside the package).  
Designed to take the BIRIO A8 aerial where required.



Card with LEDs



Wall mount



Gate post mount

## Technical data


Power supply	230 Vac / 24 Vac/dc
Power	3 W
Frequency	50 Hz
Absorption	0,006 A (230 Vac) - 0,06 A (24 Vac/dc)
Intermittent	approx. 50 cycles/min.
Service	intermittent/fixed
Temperature	-20°C +80°C
Light Intensity	50 Lux
Clear dome materials	methacrylate – OROGLAX-MFI10 shock-resistant
Weight	300 g
Protection standard	IP 53

## OVERALL DIMENSIONS

surface mount



gate post mount



BIRIO A8 aerial



Item No.	Model
4612L	MIRI 4 LED complete with fixings for wall and gate post mount

## SPECIFIC ACCESSORIES

Item No.	Description
4601L	Group of components BIRIO A8 aerial and card
4607L	RG58 Coaxial cable x 100 m
4608L	RG58 coaxial cable x 3 m