

# RAPISCAN 628XR



Easy loading conveyor and large tunnel for X-ray screening of large baggage and parcels.

Large Parcel and Small Cargo Screening

Easy Loading Conveyor

Meets Global Regulatory Requirements

Cost Effective



With a high tunnel opening and a low conveyor, the Rapiscan 628XR is designed for customers that need easy loading and unloading of small cargo as well as baggage and large parcels during the screening process for aviation check-in, air cargo and customs inspection.

With a 1,000 mm wide by 1,000 mm high tunnel opening, the Rapiscan 628XR meets the most stringent requirements of multiple global regulatory requirements including French civil aviation authority (STAC) and Civil Aviation Administration of China (CAAC).

The Rapiscan 628XR has been approved and included on the U.S. TSA Air Cargo Screening Technology List (ACSTL) applicable to U.S. TSA Certified Cargo Screening program (CCSP) as well as the Qualified Equipment and Services Lists applicable to the Transport Canada (TC) Air Cargo Security Program (ACS).

Tunnel Opening (width x height):  
1,000 x 1,000 mm (39.4 x 39.4 in)

## Standard Features

- Multi Energy Imaging (4 Color)
- View Previous/Next Bag
- Manual Image Archive
- Configurable Image Processing Keys
- Baggage Counter
- Date / Time Display
- Search Indicator
- UPS (Uninterrupted Power Supply)
- Remote Workstation
- Flat Panel Monitor

## Standard Image Processing Functions

- Crystal Clear™
- Black and White
- Organic / Inorganic Stripping
- Inverse Video
- High Penetration
- Pseudo Color
- Low Penetration
- Variable Edge Enhancement
- Variable Color Stripping
- Variable Gamma
- Variable Density
- Dynamic Continuous Zoom & Panning
- Fixed Zoom (64x)

## Automatic Detection of Explosives

Target™ automatically detects a wide range of explosives in real time during the scanning process by visibly highlighting a potential threat on the X-ray image.

## Automatic Detection of Narcotics

NARCSan™ automatically detects a wide range of narcotics in real time during the scanning process by visibly highlighting a potential threat on the X-ray image.

## Operator-Assist Tools Enables Highest Throughput

With over 13 image processing tools and multiple automatic detection functions, the feature rich software helps the operator easily and accurately detect contraband for the highest throughput and least operator fatigue.

## Industry-Leading Operator Training

Rapiscan Systems offers three comprehensive operator training programs: On-system Operator Training Program (OTP); standalone Computer Based Training software (CBT); and live in-person training with expert trainers in a one-to-one or classroom setting. All Rapiscan CBT programs are in full compliance with U.S. Transportation Security Administration (TSA) and European Union (EU) Commission Regulation 185/2010 requirements.

## Regulatory Compliance

Rapiscan 628XR image quality performance is in compliance with regulation (EC) No. 300/2008. In addition, Rapiscan 628XR Threat Image Projection (TIP) is in compliance with regulation (EU) No. 185/2010.



[www.rapiscansystems.com](http://www.rapiscansystems.com)

**Rapiscan**  
systems  
An OSI Systems Company

# RAPISCAN 628XR

## Physical Specifications

Dimensions:	Length: 3,798 mm (149.5 in.)
	Width: 1,410 mm (55.5 in.)
	Height: 2,124 mm (83.6 in.)
Tunnel Size:	1,000 mm (W) x 1,000 mm (H) (39.4 x 39.4 in.)
Conveyor Speed:	0.20 m/sec (39.4 ft./min)
Conveyor Load:	165 Kg (364 lbs) evenly distributed
Conveyor Height:	353 mm (13.9 in.)
Approx Weight:	Net: 1,250 Kg (2,756 lbs)
System Power:	115/230 VAC $\pm 10\%$ , 60/50Hz

## X-Ray Generator and Image Performance\*


Steel Penetration:	28 mm guaranteed; 30 mm typical
Wire Resolution:	38 AWG guaranteed, 40 AWG typical
Material Separation:	Low Z, Medium Z, High Z to 0.5 Z accuracy
Generator Cooling:	Sealed oil bath with forced air
Anode Voltage:	Operating at 160kV
Tube Current:	1.0 mA
Orientation:	Vertically Downward

## Operating Environment

Storage Temperature:	-20°C to 50°C
Operating Temperature:	0°C to 40°C
Relative Humidity:	5 to 95% non-condensing

## Health & Safety

Rapiscan Systems' cabinet X-ray products comply with all applicable US FDA and equivalent international regulatory agency requirements, contained in the cabinet X-ray radiation safety performance standard [21 CFR 1020.40] and the general performance standard [21 CFR Part 1010]. Rapiscan Systems certifies each cabinet X-ray product has a maximum radiation emission leakage of less 1  $\mu$ Sv/hr (0.1 mR/hr) from all external surfaces of the cabinet X-ray system.



## Options and Accessories

Target™ / Interactive Target™  
(Automatic detection of solid explosives)  
NARCSan™  
(Automatic detection of narcotics)  
Density Threshold Alert (DTA)  
Threat Image Projection (TIP)  
Threat Image Projection Network (TIPNet)  
NETView™  
(Remote network image archive review)  
NEXLink™  
(Advanced network X-ray management automation and link system)  
Multi-System Alarm Resolution Network  
Display Station (NDS)  
Automatic Image Archiving  
Enhanced Image Archiving

Computer Based Operator Training (CBT)  
Operator Training Program (OTP)  
Manual Scan  
Operator Pedestal  
Foot-mat  
Optical Operator Presence Sensor  
SmartCard Login  
Power Conditioner  
Conveyor Accessories  
Universal Printer Support

\*Stated performance as measured by Rapiscan Imaging Validation Test Kit.

With continual development of our products Rapiscan Systems reserves the right to amend specifications without notice. Product pictures are for general reference. Please note that due to US laws and regulations, not all Rapiscan products are available for sale in all countries without restriction. Please contact your Rapiscan Systems sales representative for more information.

## AMERICAS, CARIBBEAN

2805 Columbia Street  
Torrance, California 90503  
UNITED STATES of AMERICA  
Tel: +1 310-978-1457  
Fax: +1 310-349-2491

## EUROPE, MIDDLE EAST, AFRICA

X-Ray House  
Bonehurst Road  
Salfords  
Surrey RH1 5GG  
UNITED KINGDOM  
Tel: +44 (0) 870-7774301  
Fax: +44 (0) 870-7774302

## ASIA

240 Macpherson Road  
#07-01 Pines Industrial Building  
Singapore 348574  
SINGAPORE  
Tel: +65-6846-3511  
Fax: +65-6743-9915

## EMAIL

sales@rapiscansystems.com

## WEB

www.rapiscansystems.com

**Rapiscan**  
systems

An OSI Systems Company



Rapiscan Systems is  
ISO 9001:2008 Certified

ONE COMPANY - TOTAL SECURITY

www.rapiscansystems.com